



LUBRO SPEED

Synthetic oil for rapid tapping

FEATURES

It is a low viscosity, lubricating and cooling product, ideal for fast tapping and threading. The good balance between its components, allows to obtain a good processing of the piece that doesn't over-heat and forms thin chips, easily removable and a surface with quality finishes.

At the end of the operation, the residues of **LUBRO SPEED** leave a protective patina on the piece. Ideal also for operations of: boring, milling, turning, flattening, grinding and engraving.

Its low viscosity ensures rapid distribution of the product at all points in the area of interest.

The low lubricating power requires that the spraying of the product is continuous throughout the duration of the operating process.

It is suitable only for fast, non-heavy and low-grade operations.

The product is available in two versions:

LUBRO SPEED BULK. Packaged in cans from 5-30-60-120-215 Kg

LUBRO SPEED SPRAY. Packaged in spray bottle of 400 ml.

HOW TO USE

Apply the product as it is directly on the piece and on the tool before processing; make other additions at regular intervals until the completion of the same.

CHEMICAL/PHYSICAL DATA

Bulk product

| | |
|-----------------------------|---------------|
| Physical state | : liquid |
| Color | : amber |
| Density _(15°C) | : 1.05 Kg/lit |
| Solub. in water | : insoluble |
| Viscosity _(20°C) | : 0,90 cst |

Spray product

| | |
|---------------------------|----------------|
| Physical state | : Aerosol |
| Color | : amber |
| Density _(15°C) | : 0.675 Kg/lit |
| Ignition point | : +240 °C |
| Pression | : 4.5-5.5 bar |

